


**MATERIAL DATA SHEET**

Material Reference	AK7301
Description	BLACK 'PENNY STUD' RUBBER MATTING

**Description**

A general-purpose rubber matting with a Button/Penny Stud embossed pattern.

Properties	Value
Colour	Black
Hardness (Shore A)	65° ± 5°
Density (SG)	1.55 g/cm ³
Tensile Strength (Mpa)	3.0 (min)
Compression Set (22 Hours @ 70°C)	30% (max)
Elongation at Break	250% (min)
Minimum Recommended Working Temperature	-20°C
Maximum Recommended Working Temperature	+70°C
Roll/Sheet Width	1200mm
Thickness	3mm
Weight	4.5 Kg/m ²

Guidelines for use (It is the responsibility of the Customer to ensure suitability of use)

Suitable as a floor covering for temporary or semi-permanent applications in industrial and commercial environments. Also, suitable for use as shelf or drawer liners in workshop or garage environments.

Additional Information

The figures and test data on this datasheet are average values and the result of many years of tests and trials. As the company's products are used for a multiplicity of purposes, and as the company has no control over the method of their application or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for the customer's assistance only and without liability on the part of the company.