




MATERIAL DATA SHEET

Material Reference	AK597
Description	'PYRAMID' RUBBER MATTING



Description

'Pyramid' rubber matting is a general-purpose rubber matting with a high relief 'pyramid' pattern design on one side and a cloth impression pattern on the reverse.

Properties	Value
Colour	Black
Compound	NR/SBR
Hardness (Shore A)	60/70°
Density (SG)	1.4
Tensile Strength (Mpa)	3.0
Elongation (min)	150%
Abrasion Resistance (mm ³)	250
Minimum Temperature	-20°C
Maximum Temperature	+70°C
Roll/Sheet Width	1200mm
Thickness	3mm
Weight	4.2 Kg/m ²

Guidelines for use (It is the responsibility of the Customer to ensure suitability of use)

Ideally suited for walkways, tread mats, runners and general-purpose industrial applications where a multi-directional tread pattern is required.

Additional Information

Neat, attractive pattern • Easily cut to size and shape • Multi-directional tread • Non-slip when wet

The figures and test data on this datasheet are average values and the result of many years of tests and trials. As the company's products are used for a multiplicity of purposes, and as the company has no control over the method of their application or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for the customer's assistance only and without liability on the part of the company.