




MATERIAL DATA SHEET

Material Reference	AKN11
Description	FINE FLUTED RUBBER MATTING



Properties	Value
Polymer	NR/SBR
Colour	Black
Finish	Fine Ribbed Anti-Slip Top Cloth Impression Reverse
Hardness Shore 'A'	65° ± 5° Shore A
Specific Gravity	1.6 ± 0.05 g/cm ³
Tensile Strength	4 Mpa
Elongation at Break	250%
Tear Strength	12 Kg/cm
Compression Set (22 Hours @ 70°C)	43%
Minimum Continuous Working Temperature	-20°C
Maximum Continuous Working Temperature	70°C
Roll/Sheet Width	914mm / 1000mm / 1220mm

Guidelines for use *(It is the responsibility of the Customer to ensure suitability of use)*

Applications include entrance ways, walkways, production assembly lines, construction sites, work benches, van and trailer lining, dog training facilities and anywhere there is a lot of activity.

Additional Information

The figures and test data on this datasheet are average values and the result of many years of tests and trials.

As the company's products are used for a multiplicity of purposes, and as the company has no control over the method of their application or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose.

Any technical co-operation between the company and the customer is given for the customer's assistance only and without liability on the part of the company.