




MATERIAL DATA SHEET

| | |
|--------------------|--|
| Material Reference | AKN27/3 |
| Description | 1 BAR CHECKERPLATE RUBBER MATTING |



| Properties | Value |
|--|------------------------------|
| Polymer | NR/SBR |
| Colour | Black |
| Hardness Shore 'A' | 70° ± 5° Shore A |
| Specific Gravity | 1.5 ± 0.05 g/cm ³ |
| Tensile Strength | 3.5 Mpa |
| Elongation at Break | 300% |
| Abrasion (mm ³) | 480 |
| Compression Set | 43% |
| Tear Strength | 12 Kg/cm |
| Minimum Continuous Working Temperature | -20°C |
| Maximum Continuous Working Temperature | 70°C |
| Roll/Sheet Width | 1400mm |
| Thickness | 3mm |

Guidelines for use *(It is the responsibility of the Customer to ensure suitability of use)*

Applications include entrance ways, walkways, production assembly lines, construction sites, work benches, van and trailer lining, dog training facilities and anywhere there is a lot of activity.

Additional Information

The figures and test data on this datasheet are average values and the result of many years of tests and trials.

As the company's products are used for a multiplicity of purposes, and as the company has no control over the method of their application or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose.

Any technical co-operation between the company and the customer is given for the customer's assistance only and without liability on the part of the company.