



ARMORVIN® HNA

Soft PVC hose with embedded galvanised steel spiral, for suction and delivery of food liquids.



SMOOTH SURFACES



FLEXIBILITY



ABRASION RESISTANCE



TEMPERATURE RANGE

-5°C +65°C



CRUSHING RESISTANCE



FOR FOOD

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with foodstuff that requires a simulating liquid type A B C, migration tests performed at 70°C for 2 hours.

Ø I/D	Ø I/D	Ø O/D	Total Thickness	Weight	Bending Radius	Working Pressure 1:3 23°C	Bursting Pressure 23°C	Vacuum 23°C	Spiral Pitch	Spiral Direction	Ø Spiral	Coil Length
inch	mm	mm	mm	g/m	mm	bar	bar	m h2o	mm		mm	m
5/8	16	22	3	225	35	6	18	8.5	7.5	right	0.8	30
3/4	20	27	3.5	340	50	5	15	8.5	8	right	1	30
1	25	33	4	510	60	5	15	8.5	13.5	right	1.4	30
1 1/4	32	41	4.5	650	75	4.5	13.5	8.5	13.5	right	1.4	30
1 1/2	38	47	4.5	800	90	4	12	8.5	15	right	1.6	30
2	50	60	5	1200	125	3	9	8	16	right	1.8	30

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.